

COMBINATION TABLE



MU4R25

Operation	Cooling											Input(W)		
	Combination of Indoor Unit (kBtu/h Class)					Total Capacity								
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Total	Min		Rated		Max		Min	Rated	Max
1 UNIT	5				5	3,600	1.06	5,000	1.47	6,000	1.76	288	363	571
	7				7	4,200	1.23	7,000	2.05	8,400	2.46	319	478	645
	9				9	5,400	1.58	9,000	2.64	10,800	3.17	378	595	847
	12				12	7,200	2.11	12,000	3.52	14,400	4.22	478	822	1,139
	15				15	8,520	2.50	15,000	4.40	17,040	4.99	573	1,003	1,356
	18				18	10,800	3.17	18,000	5.28	21,600	6.33	747	1,302	1,827
	5	5			10	7,200	2.11	10,000	2.93	12,000	3.52	350	532	788
	5	7			12	7,200	2.11	12,000	3.52	14,400	4.22	350	669	991
	5	9			14	8,400	2.46	14,000	4.10	16,800	4.92	408	821	1,215
	7	7			14	8,400	2.46	14,000	4.10	16,800	4.92	408	821	1,215
	7	9			16	9,600	2.81	16,000	4.69	19,200	5.63	469	991	1,467
	5	12			17	10,200	2.99	17,000	4.98	20,400	5.98	532	1,083	1,603
	9	12			18	10,800	3.17	18,000	5.28	21,600	6.33	599	1,182	1,749
	7	12			19	11,400	3.34	19,000	5.57	22,800	6.68	669	1,290	1,909
	5	15			20	12,000	3.52	20,000	5.86	24,000	7.03	669	1,406	2,080
9	12			21	12,600	3.69	21,000	6.15	24,150	7.08	743	1,530	2,264	
7	15			22	13,200	3.87	22,000	6.45	25,300	7.42	743	1,638	2,425	
5	18			23	13,800	4.04	23,000	6.74	26,450	7.75	821	1,752	2,593	
9	15			24	14,400	4.22	24,000	7.03	27,000	7.91	904	1,871	2,770	
12	12			24	14,400	4.22	24,000	7.03	27,000	7.91	904	1,871	2,770	
7	18			25	14,400	4.22	24,000	7.03	27,000	7.91	904	1,871	2,770	
9	18			27	14,400	4.22	24,000	7.03	27,000	7.91	904	1,871	2,770	
12	15			27	14,400	4.22	24,000	7.03	27,000	7.91	904	1,871	2,770	
5	24			29	14,400	4.22	24,000	7.03	27,000	7.91	904	1,871	2,770	
12	18			30	14,400	4.22	24,000	7.03	27,000	7.91	904	1,871	2,770	
15	15			30	14,400	4.22	24,000	7.03	27,000	7.91	904	1,871	2,770	
7	24			31	14,400	4.22	24,000	7.03	27,000	7.91	904	1,871	2,770	
9	24			33	14,400	4.22	24,000	7.03	27,000	7.91	904	1,871	2,770	
15	18			33	14,400	4.22	24,000	7.03	27,000	7.91	904	1,871	2,770	
18	18			36	14,400	4.22	24,000	7.03	27,000	7.91	904	1,871	2,770	
12	24			36	14,400	4.22	24,000	7.03	27,000	7.91	904	1,871	2,770	
15	24			39	14,400	4.22	24,000	7.03	27,000	7.91	904	1,871	2,770	
5	5	5		15	9,000	2.64	15,000	4.40	18,000	5.28	422	837	1,239	
5	5	7		17	10,200	2.99	17,000	4.98	20,400	5.98	481	1,013	1,500	
5	5	9		19	11,400	3.34	19,000	5.57	22,800	6.68	544	1,212	1,794	
5	7	7		19	11,400	3.34	19,000	5.57	22,800	6.68	544	1,212	1,794	
5	7	9		21	12,600	3.69	21,000	6.15	25,200	7.39	682	1,438	2,128	
7	7	7		21	12,600	3.69	21,000	6.15	25,200	7.39	682	1,438	2,128	
5	5	12		22	13,200	3.87	22,000	6.45	26,400	7.74	731	1,540	2,279	
5	9	9		23	13,800	4.04	23,000	6.74	27,600	8.09	731	1,647	2,437	
7	7	9		23	13,800	4.04	23,000	6.74	27,600	8.09	731	1,647	2,437	
5	7	12		24	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
5	5	15		25	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
7	9	9		25	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
5	9	12		26	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
7	7	12		26	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
5	7	15		27	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
9	9	9		27	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
7	9	12		28	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
5	5	18		28	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
5	9	15		29	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
5	12	12		29	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
7	7	15		29	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
5	7	18		30	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
9	9	12		30	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
7	9	15		31	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
7	12	12		31	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
5	12	15		32	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
5	9	18		32	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
7	7	18		32	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
9	9	15		33	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
9	12	12		33	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
7	9	18		34	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
7	12	15		34	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
5	5	24		34	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
5	12	18		35	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
5	15	15		35	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
5	7	24		36	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
9	12	15		36	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
12	12	12		36	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
9	9	18		36	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
7	12	18		37	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
7	15	15		37	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
5	9	24		38	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
5	15	18		38	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
7	7	24		38	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
9	12	18		39	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
9	15	15		39	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	
12	12	15		39	14,400	4.22	24,000	7.03	29,000	8.50	837	1,758	2,603	

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

COMBINATION TABLE



Operation	Cooling											Input(W)		
	Combination of Indoor Unit (kBtu/h Class)					Total Capacity								
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Total	Min		Rated		Max		Min	Rated	Max
1 UNIT	5				5	3,600	1.06	5,000	1.47	6,000	1.76	288	363	571
	7				7	4,200	1.23	7,000	2.05	8,400	2.46	319	478	645
	9				9	5,400	1.58	9,000	2.64	10,800	3.17	378	595	847
	12				12	7,200	2.11	12,000	3.52	14,400	4.22	478	822	1,139
	15				15	8,520	2.50	15,000	4.40	17,040	4.99	573	1,003	1,356
	18				18	10,800	3.17	18,000	5.28	21,600	6.33	747	1,302	1,827
	5	5			10	7,200	2.11	10,000	2.93	12,000	3.52	350	532	788
	5	7			12	7,200	2.11	12,000	3.52	14,400	4.22	350	669	991
	5	9			14	8,400	2.46	14,000	4.10	16,800	4.92	408	821	1,215
	7	7			14	8,400	2.46	14,000	4.10	16,800	4.92	408	821	1,215
	7	9			16	9,600	2.81	16,000	4.69	19,200	5.63	469	991	1,467
	5	12			17	10,200	2.99	17,000	4.98	20,400	5.98	532	1,083	1,603
	9	12			18	10,800	3.17	18,000	5.28	21,600	6.33	599	1,182	1,749
	7	12			19	11,400	3.34	19,000	5.57	22,800	6.68	669	1,290	1,909
	5	15			20	12,000	3.52	20,000	5.86	24,000	7.03	669	1,406	2,080
9	12			21	12,600	3.69	21,000	6.15	24,150	7.08	743	1,530	2,264	
7	15			22	13,200	3.87	22,000	6.45	25,300	7.42				

COMBINATION TABLE



MU4R25

Operation	Heating											Input(W)		
	Combination of Indoor Unit (kBtu/h Class)					Total Capacity								
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Total	Min		Rated		Max		Min	Rated	Max
1 UNIT	5				5	4,000	1.17	5,500	1.61	6,325	1.85	279	384	589
	7				7	5,040	1.48	8,400	2.46	9,660	2.83	342	579	743
	9				9	6,480	1.90	10,800	3.17	12,420	3.64	483	757	997
	12				12	7,920	2.32	13,200	3.87	15,180	4.45	537	954	1,234
	15				15	9,900	2.90	16,500	4.84	18,975	5.56	688	1,189	1,593
	18				18	11,880	3.48	19,800	5.80	22,770	6.67	845	1,483	1,978
	24				24	15,240	4.47	25,400	7.44	26,670	7.82	1,101	1,840	2,377
	5	5			10	7,200	2.11	12,000	3.52	14,400	4.22	329	598	861
	5	7			12	8,640	2.53	14,400	4.22	17,280	5.06	430	904	1,301
	5	9			14	10,080	2.95	16,800	4.92	20,160	5.91	484	945	1,360
	5	12			16	11,520	3.38	19,200	5.63	23,040	6.75	540	1,118	1,610
	5	15			17	12,240	3.59	20,400	5.98	24,480	7.17	598	1,319	1,899
5	18			18	12,960	3.80	21,600	6.33	25,920	7.60	660	1,430	2,059	
5	24			19	13,680	4.01	22,800	6.68	27,360	8.02	725	1,543	2,221	
5	15	5		20	14,400	4.22	24,000	7.03	28,800	8.44	764	1,662	2,393	
5	12	7		21	15,120	4.43	25,200	7.39	29,000	8.50	793	1,749	2,518	
5	9	9		22	15,840	4.64	26,400	7.74	29,000	8.50	867	1,836	2,644	
5	18	9		23	16,560	4.85	27,600	8.09	29,000	8.50	945	1,977	2,850	
5	15	12		24	16,560	4.85	27,600	8.09	29,000	8.50	945	1,977	2,850	
5	12	15		24	16,560	4.85	27,600	8.09	29,000	8.50	945	1,977	2,850	
5	9	18		24	16,560	4.85	27,600	8.09	29,000	8.50	945	1,977	2,850	
5	12	15	5	27	16,560	4.85	27,600	8.09	29,000	8.50	945	1,977	2,850	
5	12	18		27	16,560	4.85	27,600	8.09	29,000	8.50	945	1,977	2,850	
5	12	15	7	27	16,560	4.85	27,600	8.09	29,000	8.50	945	1,977	2,850	
5	12	18	7	29	16,560	4.85	27,600	8.09	29,000	8.50	945	1,977	2,850	
5	15	18		30	16,560	4.85	27,600	8.09	29,000	8.50	945	1,977	2,850	
5	15	12	7	31	16,560	4.85	27,600	8.09	29,000	8.50	945	1,977	2,850	
5	18	12	7	33	16,560	4.85	27,600	8.09	29,000	8.50	945	1,977	2,850	
5	15	18	7	33	16,560	4.85	27,600	8.09	29,000	8.50	945	1,977	2,850	
5	18	15	7	36	16,560	4.85	27,600	8.09	29,000	8.50	945	1,977	2,850	
5	12	24		36	16,560	4.85	27,600	8.09	29,000	8.50	945	1,977	2,850	
5	15	24		39	16,560	4.85	27,600	8.09	29,000	8.50	945	1,977	2,850	
5	5	5	5	15	10,800	3.17	18,000	5.28	21,600	6.33	497	946	1,363	
5	5	7	7	17	12,240	3.59	20,400	5.98	24,480	7.17	551	1,118	1,610	
5	5	9	9	19	13,680	4.01	22,800	6.68	27,360	8.02	725	1,419	2,044	
5	7	7	9	19	13,680	4.01	22,800	6.68	27,360	8.02	725	1,419	2,044	
5	7	9	7	21	15,120	4.43	25,200	7.39	30,240	8.86	730	1,610	2,319	
5	7	7	7	21	15,120	4.43	25,200	7.39	30,240	8.86	730	1,610	2,319	
5	5	5	12	22	15,840	4.64	26,400	7.74	31,000	9.09	798	1,697	2,444	
5	5	9	9	23	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	7	7	9	23	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	7	12		24	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	5	5	15	25	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	7	9	9	25	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	9	12		26	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	7	7	12	26	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	7	15		27	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	9	9	9	27	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	9	12		28	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	9	15		28	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	9	18		29	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	12	12		29	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	7	7	15	29	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	7	18		30	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	9	9	12	30	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	7	9	15	31	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	7	12	12	31	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	5	12	15	32	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	9	18		32	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	7	7	18	32	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	9	9	15	33	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	9	12	12	33	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	7	9	18	34	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	7	12	15	34	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	5	5	24	34	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	5	12	18	35	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	5	15	15	35	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	5	7	24	36	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	9	12	15	36	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	12	12	12	36	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	9	9	18	36	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	7	12	18	37	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	7	15	15	37	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	9	24		38	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	15	18		38	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	7	7	24	38	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	9	12	18	39	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	9	15	15	39	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	
5	12	12	15	39	16,560	4.85	27,600	8.09	31,000	9.09	870	1,838	2,647	

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

COMBINATION TABLE



Operation	Heating											Input(W)		
	Combination of Indoor Unit (kBtu/h Class)					Total Capacity								
	UNIT-A	UNIT-B	UNIT-C	UNIT-D	Total	Min		Rated		Max		Min	Rated	Max
1 UNIT	5				5	4,000	1.17	5,500	1.61	6,325	1.85	279	384	589
	7				7	5,040	1.48	8,400	2.46	9,660	2.83	342	579	743
	9				9	6,480	1.90	10,800	3.17	12,420	3.64	483	757	997
	12				12	7,920	2.32	13,200	3.87	15,180	4.45	537	954	1,234
	15				15	9,900	2.90	16,500	4.84	18,975	5.56	688	1,189	1,593
	18				18	11,880	3.48	19,800	5.80	22,770	6.67	845	1,483	1,978
	24				24	15,240	4.47	25,400	7.44	26,670	7.82	1,101	1,840	2,377
	5	5			10	7,200	2.11	12,000	3.52	14,400	4.22	329	598	861
	5	7			12	8,640	2.53	14,400	4.22	17,280	5.06	430	904	1,301
	5	9			14	10,080	2.95	16,800	4.92	20,160	5.91	484	945	1,360
	5	12			16	11,520	3.38	19,200	5.63	23,040	6.75	540	1,118	1,610
	5	15			17	12,240	3.59	20,400	5.98	24,480	7.17	598	1,319	1,899
5	18			18	12,960	3.80	21,600	6.33	25,920	7.60	660	1,430	2,059	
5	24													